

Description:

KMP is biaxially oriented polyester (BOPET) films with chemical coated side metallized. High barrier flexible packages for: coffee, dehydrated food, frozen food, lidding, snacks, etc.


Features and applications:

- * Excellent machinability
- Unprotected metallized side must be not in contact with foods.
- * Superior adhesion with different inks and coating materials
- * The choice of laminating type and lamination adhesives, which can effect the metal adhesion force after application, is based on customer's knowledge and experience.

Available gauge(s) (µm): 12 KMP needs to be stocked in a closed warehouse and preserved from the light. Polinas will not accept any responsibilty for material older than 1 year from the delivery



BOPET FILMS



Properties	Unit	t	Technical Values	Test Method
Thickness	μm		12	ASTM D 2673
Yield	m2/kg		59,95	ASTM D 2673
Optical density	%		2,3	POLINAS
Dimensional stability	%	MD	=< 1,5	ASTM D 1204
	%	TD	=< 1	
Tensile strength at break	kg/mm²	MD	22	ASTM D 882
	kg/mm²	TD	25	
Elongation	%	MD	120	ASTM D 882
	%	TD	110	
C.O.F		BB	=< 0,5	ASTM D 1894
OTR (23C, 0%RH)	cm3/m2/24h		1	ASTM D 3985
WVTR (38C, 90%RH)	gr/m2/24h		0,5	ASTM F 1249

This film complies with the EC and FDA food contact regulations. Detailed documentation is available on your request. All the information contained in this datasheet is supplied at the best of our knowledge and must not be construed as a guarantee. Since the circumstances and processes used in the application of our product are beyond our control, our guarantee remains within the limits of the generic conditions of supply of the product itself. Business Development and Customer Solutions Department is available to supply upon request all the updated recommendations relevant to the best converting and processing techniques for the product. Also, different film thicknesses and properties are available upon request.









Date : 28.02.2025